
influxdb*client*

Release 1.14.0

Jan 29, 2021

Contents:

1	User Guide	1
1.1	Query	2
1.2	Pandas DataFrame	2
1.3	Write	3
1.3.1	The data could be written as	3
1.3.2	Batching	3
1.3.3	Default Tags	5
1.3.4	Asynchronous client	6
1.3.5	Synchronous client	7
1.4	Queries	7
1.4.1	Pandas DataFrame	8
1.5	Examples	9
1.5.1	How to efficiently import large dataset	9
1.6	Delete data	11
1.7	Gzip support	12
1.8	Debugging	12
2	API Reference	13
2.1	InfluxDBClient	13
2.2	QueryApi	15
2.3	WriteApi	17
2.4	BucketsApi	17
2.5	LabelsApi	20
2.6	OrganizationsApi	21
2.7	UsersApi	22
2.8	TasksApi	23
2.9	DeleteApi	28
3	InfluxDB 2.0 client features	31
4	Installation	33
4.1	pip install	33
4.2	Setuptools	33
5	Getting Started	35
6	Client configuration	37

6.1	Via File	37
6.2	Via Environment Properties	37
7	Indices and tables	39
	Index	41

- *Query*
- *Pandas DataFrame*
- *Write*
 - *The data could be written as*
 - *Batching*
 - *Default Tags*
 - * *Via API*
 - * *Via Configuration file*
 - * *Via Environment Properties*
 - *Asynchronous client*
 - *Synchronous client*
- *Queries*
 - *Pandas DataFrame*
- *Examples*
 - *How to efficiently import large dataset*
- *Delete data*
- *Gzip support*
- *Debugging*

1.1 Query

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, record=p)

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print (row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1
```

1.2 Pandas DataFrame

Note: For DataFrame querying you should install Pandas dependency via `pip install influxdb-client[extra]`.

Note: Note that if a query returns more than one table then the client generates a DataFrame for each of them.

The client is able to retrieve data in Pandas DataFrame format through `query_data_frame`:

```
from influxdb_client import InfluxDBClient, Point, Dialect
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

"""
Prepare data
```

(continues on next page)

(continued from previous page)

```

"""
_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
→ 3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

"""
Query: using Pandas DataFrame
"""
data_frame = query_api.query_data_frame('from(bucket:"my-bucket") '
                                         '|> range(start: -10m) '
                                         '|> pivot(rowKey:["_time"], columnKey: ["_
→ field"], valueColumn: "_value") '
                                         '|> keep(columns: ["location", "temperature"])
→ ')
print(data_frame.to_string())

"""
Close client
"""
client.__del__()

```

Output:

1.3 Write

The `WriteApi` supports synchronous, asynchronous and batching writes into InfluxDB 2.0. The data should be passed as a `InfluxDB Line Protocol`, `Data Point` or `Observable` stream.

Important: The `WriteApi` in batching mode (default mode) is suppose to run as a singleton. To flush all your data you should call “`_write_client.close()`” at the end of your script.

The default instance of `WriteApi` use batching.

1.3.1 The data could be written as

1. string or bytes that is formatted as a InfluxDB's line protocol
2. `Data Point` structure
3. Dictionary style mapping with keys: measurement, tags, fields and time
4. List of above items
5. A batching type of write also supports an `Observable` that produce one of an above item
6. `Pandas DataFrame`

1.3.2 Batching

The batching is configurable by `write_options`:

Property	Description	Default Value
batch_size	the number of data points to collect in a batch	1000
flush_interval	the number of milliseconds before the batch is written	1000
jitter_interval	the number of milliseconds to increase the batch flush interval by a random amount	0
retry_interval	the number of milliseconds to retry unsuccessful write. The retry interval is used when the InfluxDB server does not specify "Retry-After" header.	5000
max_retries	the number of max retries when write fails	3
max_retry_delay	maximum delay between each retry attempt in milliseconds	180_000
exponential_base	the base for the exponential retry delay, the next delay is computed as $\text{retry_interval} * \text{exponential_base}^{(\text{attempts}-1)} + \text{random}(\text{jitter_interval})$	5

```

import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions
from influxdb_client.client.write_api import SYNCHRONOUS

_client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
_write_client = _client.write_api(write_options=WriteOptions(batch_size=500,
                                                             flush_interval=10_000,
                                                             jitter_interval=2_000,
                                                             retry_interval=5_000,
                                                             max_retries=5,
                                                             max_retry_delay=30_000,
                                                             exponential_base=2))

"""
Write Line Protocol formatted as string
"""
_write_client.write("my-bucket", "my-org", "h2o_feet,location=coyote_creek water_
↪level=1.0 1")
_write_client.write("my-bucket", "my-org", ["h2o_feet,location=coyote_creek water_
↪level=2.0 2",
                                           "h2o_feet,location=coyote_creek water_
↪level=3.0 3"])

"""
Write Line Protocol formatted as byte array
"""
_write_client.write("my-bucket", "my-org", "h2o_feet,location=coyote_creek water_
↪level=1.0 1".encode())
_write_client.write("my-bucket", "my-org", ["h2o_feet,location=coyote_creek water_
↪level=2.0 2".encode(),
                                           "h2o_feet,location=coyote_creek water_
↪level=3.0 3".encode()])

"""
Write Dictionary-style object
"""
_write_client.write("my-bucket", "my-org", {"measurement": "h2o_feet", "tags": {
↪"location": "coyote_creek"},

```

(continues on next page)

(continued from previous page)

```

        "fields": {"water_level": 1.0}, "time": 1}
    ↪)
_write_client.write("my-bucket", "my-org", [{"measurement": "h2o_feet", "tags": {
    ↪"location": "coyote_creek"},
        "fields": {"water_level": 2.0}, "time": 2}
    ↪,
        {"measurement": "h2o_feet", "tags": {
    ↪"location": "coyote_creek"},
        "fields": {"water_level": 3.0}, "time": 3}
    ↪])

"""
Write Data Point
"""
_write_client.write("my-bucket", "my-org", Point("h2o_feet").tag("location", "coyote_
    ↪creek").field("water_level", 4.0).time(4))
_write_client.write("my-bucket", "my-org", [Point("h2o_feet").tag("location", "coyote_
    ↪creek").field("water_level", 5.0).time(5),
        Point("h2o_feet").tag("location", "coyote_
    ↪creek").field("water_level", 6.0).time(6)])

"""
Write Observable stream
"""
_data = rx \
    .range(7, 11) \
    .pipe(ops.map(lambda i: "h2o_feet,location=coyote_creek water_level={0}.0 {0}".
    ↪format(i)))

_write_client.write("my-bucket", "my-org", _data)

"""
Write Pandas DataFrame
"""
_now = pd.Timestamp().now('UTC')
_data_frame = pd.DataFrame(data=[["coyote_creek", 1.0], ["coyote_creek", 2.0]],
                           index=[now, now + timedelta(hours=1)],
                           columns=["location", "water_level"])

_write_client.write(bucket.name, record=data_frame, data_frame_measurement_name='h2o_
    ↪feet',
                    data_frame_tag_columns=['location'])

"""
Close client
"""
_write_client.__del__()
_client.__del__()

```

1.3.3 Default Tags

Sometimes is useful to store same information in every measurement e.g. hostname, location, customer. The client is able to use static value or env property as a tag value.

The expressions:

- California Miner - static value
- `${env.hostname}` - environment property

Via API

```
point_settings = PointSettings()
point_settings.add_default_tag("id", "132-987-655")
point_settings.add_default_tag("customer", "California Miner")
point_settings.add_default_tag("data_center", "${env.data_center}")

self.write_client = self.client.write_api(write_options=SYNCHRONOUS, point_
↪ settings=point_settings)
```

```
self.write_client = self.client.write_api(write_options=SYNCHRONOUS,
                                           point_settings=PointSettings(**{"id":
↪ "132-987-655",
↪ "customer": "California Miner"}))
```

Via Configuration file

In a ini configuration file you are able to specify default tags by tags segment.

```
self.client = InfluxDBClient.from_config_file("config.ini")
```

Via Environment Properties

You are able to specify default tags by environment properties with prefix `INFLUXDB_V2_TAG_`.

Examples:

- `INFLUXDB_V2_TAG_ID`
- `INFLUXDB_V2_TAG_HOSTNAME`

```
self.client = InfluxDBClient.from_env_properties()
```

1.3.4 Asynchronous client

Data are writes in an asynchronous HTTP request.

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import ASYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
write_api = client.write_api(write_options=ASYNCHRONOUS)

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪ 3)

async_result = write_api.write(bucket="my-bucket", record=[_point1, _point2])
```

(continues on next page)

(continued from previous page)

```

async_result.get()

client.__del__()

```

1.3.5 Synchronous client

Data are writes in a synchronous HTTP request.

```

from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
write_api = client.write_api(write_options=SYNCHRONOUS)

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪ 3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

client.__del__()

```

1.4 Queries

The result retrieved by `QueryApi` could be formatted as a:

1. Flux data structure: `FluxTable`, `FluxColumn` and `FluxRecord`
2. `csv.reader` which will iterate over CSV lines
3. Raw unprocessed results as a `str` iterator
4. `Pandas DataFrame`

The API also support streaming `FluxRecord` via `query_stream`, see example below:

```

from influxdb_client import InfluxDBClient, Point, Dialect
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

"""
Prepare data
"""

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪ 3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

```

(continues on next page)

(continued from previous page)

```

"""
Query: using Table structure
"""
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for record in table.records:
        print(record.values)

print()
print()

"""
Query: using Stream
"""
records = query_api.query_stream('from(bucket:"my-bucket") |> range(start: -10m)')

for record in records:
    print(f'Temperature in {record["location"]} is {record["_value"]}')

"""
Interrupt a stream after retrieve a required data
"""
large_stream = query_api.query_stream('from(bucket:"my-bucket") |> range(start: -100d)
↪')
for record in large_stream:
    if record["location"] == "New York":
        print(f'New York temperature: {record["_value"]}')
        break

large_stream.close()

print()
print()

"""
Query: using csv library
"""
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)',
                                  dialect=Dialect(header=False, delimiter=",", comment_
↪prefix="#", annotations=[],
                                  date_time_format="RFC3339"))

for csv_line in csv_result:
    if not len(csv_line) == 0:
        print(f'Temperature in {csv_line[9]} is {csv_line[6]}')

"""
Close client
"""
client.__del__()

```

1.4.1 Pandas DataFrame

Note: For DataFrame querying you should install Pandas dependency via `pip install influxdb-client[extra]`.

Note: Note that if a query returns more then one table then the client generates a DataFrame for each of them.

The client is able to retrieve data in **Pandas DataFrame** format through `query_data_frame`:

```
from influxdb_client import InfluxDBClient, Point, Dialect
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

"""
Prepare data
"""

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

"""
Query: using Pandas DataFrame
"""
data_frame = query_api.query_data_frame('from(bucket:"my-bucket") '
                                         '|> range(start: -10m) '
                                         '|> pivot(rowKey:["_time"], columnKey: ["_
↪field"], valueColumn: "_value") '
                                         '|> keep(columns: ["location", "temperature"])
↪')
print(data_frame.to_string())

"""
Close client
"""
client.__del__()
```

Output:

1.5 Examples

1.5.1 How to efficiently import large dataset

The following example shows how to import dataset with dozen megabytes. If you would like to import gigabytes of data then use our multiprocessing example: `import_data_set_multiprocessing.py` for use a full capability of your hardware.

- sources - `import_data_set.py`

```

"""
Import VIX - CBOE Volatility Index - from "vix-daily.csv" file into InfluxDB 2.0

https://datahub.io/core/finance-vix#data
"""

from collections import OrderedDict
from csv import DictReader

import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions

def parse_row(row: OrderedDict):
    """Parse row of CSV file into Point with structure:

        financial-analysis,type=ily close=18.47,high=19.82,low=18.28,open=19.82,
↪11981952000000000000

    CSV format:
        Date,VIX Open,VIX High,VIX Low,VIX Close\n
        2004-01-02,17.96,18.68,17.54,18.22\n
        2004-01-05,18.45,18.49,17.44,17.49\n
        2004-01-06,17.66,17.67,16.19,16.73\n
        2004-01-07,16.72,16.75,15.5,15.5\n
        2004-01-08,15.42,15.68,15.32,15.61\n
        2004-01-09,16.15,16.88,15.57,16.75\n
        ...

    :param row: the row of CSV file
    :return: Parsed csv row to [Point]
    """

    """
    For better performance is sometimes useful directly create a LineProtocol to,
↪avoid unnecessary escaping overhead:
    """

    # from pytz import UTC
    # import ciso8601
    # from influxdb_client.client.write.point import EPOCH
    #
    # time = (UTC.localize(ciso8601.parse_datetime(row["Date"])) - EPOCH).total_
↪seconds() * 1e9
    # return f"financial-analysis,type=vix-daily" \
    #       f" close={float(row['VIX Close'])},high={float(row['VIX High'])},low=
↪{float(row['VIX Low'])},open={float(row['VIX Open'])} " \
    #       f" {int(time)}"

    return Point("financial-analysis") \
        .tag("type", "vix-daily") \
        .field("open", float(row['VIX Open'])) \
        .field("high", float(row['VIX High'])) \
        .field("low", float(row['VIX Low'])) \
        .field("close", float(row['VIX Close'])) \
        .time(row['Date'])

```

(continues on next page)

(continued from previous page)

```

"""
Converts vix-daily.csv into sequence of datad point
"""
data = rx \
    .from_iterable(DictReader(open('vix-daily.csv', 'r'))) \
    .pipe(ops.map(lambda row: parse_row(row)))

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org",
    debug=True)

"""
Create client that writes data in batches with 50_000 items.
"""
write_api = client.write_api(write_options=WriteOptions(batch_size=50_000, flush_
    interval=10_000))

"""
Write data into InfluxDB
"""
write_api.write(bucket="my-bucket", record=data)
write_api.__del__()

"""
Querying max value of CBOE Volatility Index
"""
query = 'from(bucket:"my-bucket")' \
    ' |> range(start: 0, stop: now())' \
    ' |> filter(fn: (r) => r._measurement == "financial-analysis")' \
    ' |> max()'
result = client.query_api().query(query=query)

"""
Processing results
"""
print()
print("=== results ===")
print()
for table in result:
    for record in table.records:
        print('max {0:5} = {1}'.format(record.get_field(), record.get_value()))

"""
Close client
"""
client.__del__()

```

1.6 Delete data

The `delete_api.py` supports deletes points from an InfluxDB bucket.

```

from influxdb_client import InfluxDBClient

client = InfluxDBClient(url="http://localhost:8086", token="my-token")

```

(continues on next page)

(continued from previous page)

```
delete_api = client.delete_api()

"""
Delete Data
"""
start = "1970-01-01T00:00:00Z"
stop = "2021-02-01T00:00:00Z"
delete_api.delete(start, stop, '_measurement="my_measurement"', bucket='my-bucket',
↳org='my-org')

"""
Close client
"""
client.__del__()
```

1.7 Gzip support

InfluxDBClient does not enable gzip compression for http requests by default. If you want to enable gzip to reduce transfer data's size, you can call:

```
from influxdb_client import InfluxDBClient

_db_client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org"
↳, enable_gzip=True)
```

1.8 Debugging

For debug purpose you can enable verbose logging of http requests. Both request header and body will be logged to standard output.

```
_client = InfluxDBClient(url="http://localhost:8086", token="my-token", debug=True,
↳org="my-org")
```


- *InfluxDBClient*
- *QueryApi*
- *WriteApi*
- *BucketsApi*
- *LabelsApi*
- *OrganizationsApi*
- *UsersApi*
- *TasksApi*
- *DeleteApi*

2.1 InfluxDBClient

```
class influxdb_client.InfluxDBClient(url, token, debug=None, timeout=10000, enable_gzip=False, org: str = None, default_tags: dict = None, **kwargs)
```

InfluxDBClient is client for InfluxDB v2.

Initialize defaults.

Parameters

- **url** – InfluxDB server API url (ex. <http://localhost:8086>).
- **token** – auth token
- **debug** – enable verbose logging of http requests

- **timeout** – default http client timeout
- **enable_gzip** – Enable Gzip compression for http requests. Currently only the “Write” and “Query” endpoints supports the Gzip compression.
- **org** – organization name (used as a default in query and write API)

Key bool verify_ssl Set this to false to skip verifying SSL certificate when calling API from https server.

Key str ssl_ca_cert Set this to customize the certificate file to verify the peer.

Key str proxy Set this to configure the http proxy to be used (ex. <http://localhost:3128>)

Key urllib3.util.retry.Retry retries Set the default retry strategy that is used for all HTTP requests except batching writes. As a default there is no one retry strategy.

authorizations_api () → influxdb_client.client.authorizations_api.AuthorizationsApi
Create the Authorizations API instance.

Returns authorizations api

buckets_api () → influxdb_client.client.bucket_api.BucketsApi
Create the Bucket API instance.

Returns buckets api

close ()
Shutdown the client.

delete_api () → influxdb_client.client.delete_api.DeleteApi
Get the delete metrics API instance.

Returns delete api

classmethod from_config_file (config_file: str = 'config.ini', debug=None, enable_gzip=False)
Configure client via ‘*.ini’ file in segment ‘influx2’.

Supported options:

- url
- org
- token
- timeout,
- verify_ssl
- ssl_ca_cert

classmethod from_env_properties (debug=None, enable_gzip=False)
Configure client via environment properties.

Supported environment properties:

- INFLUXDB_V2_URL
- INFLUXDB_V2_ORG
- INFLUXDB_V2_TOKEN
- INFLUXDB_V2_TIMEOUT
- INFLUXDB_V2_VERIFY_SSL
- INFLUXDB_V2_SSL_CA_CERT

health() → influxdb_client.domain.health_check.HealthCheck
Get the health of an instance.

Returns HealthCheck

labels_api() → influxdb_client.client.labels_api.LabelsApi
Create the Labels API instance.

Returns labels api

organizations_api() → influxdb_client.client.organizations_api.OrganizationsApi
Create the Organizations API instance.

Returns organizations api

query_api() → influxdb_client.client.query_api.QueryApi
Create a Query API instance.

Returns Query api instance

ready() → influxdb_client.domain.ready.Ready
Get The readiness of the InfluxDB 2.0.

Returns Ready

tasks_api() → influxdb_client.client.tasks_api.TasksApi
Create the Tasks API instance.

Returns tasks api

users_api() → influxdb_client.client.users_api.UsersApi
Create the Users API instance.

Returns users api

write_api(write_options=<influxdb_client.client.write_api.WriteOptions object>, point_settings=<influxdb_client.client.write_api.PointSettings object>) → influxdb_client.client.write_api.WriteApi
Create a Write API instance.

Parameters

- **point_settings** –
- **write_options** – write api configuration

Returns write api instance

2.2 QueryApi

class influxdb_client.**QueryApi**(influxdb_client)
Implementation for '/api/v2/query' endpoint.
Initialize query client.

Parameters **influxdb_client** – influxdb client

query(query: str, org=None) → List[influxdb_client.client.flux_table.FluxTable]
Execute synchronous Flux query and return result as a List['FluxTable'].

Parameters

- **query** – the Flux query

- **org** – organization name (optional if already specified in InfluxDBClient)

Returns

query_csv (*query: str, org=None, dialect: influxdb_client.domain.dialect.Dialect = {'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True}*)

Execute the Flux query and return results as a CSV iterator. Each iteration returns a row of the CSV file.

Parameters

- **query** – a Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns The returned object is an iterator. Each iteration returns a row of the CSV file (which can span multiple input lines).

query_data_frame (*query: str, org=None, data_frame_index: List[str] = None*)

Execute synchronous Flux query and return Pandas DataFrame.

Note that if a query returns more than one table then the client generates a DataFrame for each of them.

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **data_frame_index** – the list of columns that are used as DataFrame index

Returns

query_data_frame_stream (*query: str, org=None, data_frame_index: List[str] = None*)

Execute synchronous Flux query and return stream of Pandas DataFrame as a Generator[`pd.DataFrame`].

Note that if a query returns more than one table then the client generates a DataFrame for each of them.

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **data_frame_index** – the list of columns that are used as DataFrame index

Returns

query_raw (*query: str, org=None, dialect={'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True}*)

Execute synchronous Flux query and return result as raw unprocessed result as a str.

Parameters

- **query** – a Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns

 str

query_stream (*query: str, org=None*) → Generator[[`influxdb_client.client.flux_table.FluxRecord`, Any], None]

Execute synchronous Flux query and return stream of FluxRecord as a Generator[`'FluxRecord'`].

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)

Returns

2.3 WriteApi

```
class influxdb_client.WriteApi (influxdb_client, write_options: influxdb_client.client.write_api.WriteOptions = <influxdb_client.client.write_api.WriteOptions object>, point_settings: influxdb_client.client.write_api.PointSettings = <influxdb_client.client.write_api.PointSettings object>)
```

Implementation for '/api/v2/write' endpoint.

Initialize defaults.

close()

Flush data and dispose a batching buffer.

flush()

Flush data.

write (bucket: str, org: str = None, record: Union[str, Iterable[str], influxdb_client.client.write_point.Point, Iterable[Point], dict, Iterable[dict], bytes, Iterable[bytes], rx.core.observable.observable.Observable] = None, write_precision: influxdb_client.domain.write_precision.WritePrecision = 'ns', **kwargs) → Any

Write time-series data into InfluxDB.

Parameters

- **org** (str) – specifies the destination organization for writes; take either the ID or Name interchangeably; if both orgID and org are specified, org takes precedence. (required)
- **bucket** (str) – specifies the destination bucket for writes (required)
- **write_precision** (WritePrecision) – specifies the precision for the unix timestamps within the body line-protocol. The precision specified on a Point has precedence and is use for write.
- **record** – Points, line protocol, Pandas DataFrame, RxPY Observable to write

Key data_frame_measurement_name name of measurement for writing Pandas DataFrame

Key data_frame_tag_columns list of DataFrame columns which are tags, rest columns will be fields

2.4 BucketsApi

```
class influxdb_client.BucketsApi (influxdb_client)
```

Implementation for '/api/v2/buckets' endpoint.

Initialize defaults.

create_bucket (bucket=None, bucket_name=None, org_id=None, retention_rules=None, description=None) → influxdb_client.domain.bucket.Bucket

Create a bucket.

Parameters

- **bucket** (*Bucket*) – bucket to create (required)
- **bucket_name** – bucket name
- **description** – bucket description
- **org_id** – org_id
- **bucket_name** – bucket name
- **retention_rules** – retention rules array or single *BucketRetentionRules*

Returns *Bucket* If the method is called asynchronously, returns the request thread.

delete_bucket (*bucket*)

Delete a bucket.

Parameters **bucket** – bucket id or *Bucket*

Returns *Bucket* If the method is called asynchronously, returns the request thread.

find_bucket_by_id (*id*)

Find bucket by ID.

Parameters **id** –

Returns

find_bucket_by_name (*bucket_name*)

Find bucket by name.

Parameters **bucket_name** – bucket name

Returns *Bucket*

find_buckets ()

Get all buckets.

```
class influxdb_client.domain.Bucket (links=None, id=None, type='user', name=None,
                                     description=None, org_id=None, rp=None,
                                     created_at=None, updated_at=None, reten-
                                     tion_rules=None, labels=None)
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Bucket - a model defined in OpenAPI.

created_at

Get the created_at of this Bucket.

Returns The created_at of this Bucket.

Return type *datetime*

description

Get the description of this Bucket.

Returns The description of this Bucket.

Return type *str*

id

Get the id of this Bucket.

Returns The id of this Bucket.

Return type `str`

labels

Get the labels of this Bucket.

Returns The labels of this Bucket.

Return type `list[Label]`

links

Get the links of this Bucket.

Returns The links of this Bucket.

Return type `BucketLinks`

name

Get the name of this Bucket.

Returns The name of this Bucket.

Return type `str`

org_id

Get the org_id of this Bucket.

Returns The org_id of this Bucket.

Return type `str`

retention_rules

Get the retention_rules of this Bucket.

Rules to expire or retain data. No rules means data never expires.

Returns The retention_rules of this Bucket.

Return type `list[BucketRetentionRules]`

rp

Get the rp of this Bucket.

Returns The rp of this Bucket.

Return type `str`

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

type

Get the type of this Bucket.

Returns The type of this Bucket.

Return type `str`

updated_at

Get the updated_at of this Bucket.

Returns The updated_at of this Bucket.

Return type `datetime`

2.5 LabelsApi

class influxdb_client.LabelsApi (influxdb_client)

Implementation for '/api/v2/labels' endpoint.

Initialize defaults.

clone_label (cloned_name: str, label: influxdb_client.domain.label.Label) → influxdb_client.domain.label.Label
Create the new instance of the label as a copy existing label.

Parameters

- **cloned_name** – new label name
- **label** – existing label

Returns cloned Label

create_label (name: str, org_id: str, properties: Dict[str, str] = None) → influxdb_client.domain.label.Label
Create a new label.

Parameters

- **name** – label name
- **org_id** – organization id
- **properties** – optional label properties

Returns created label

delete_label (label: Union[str, influxdb_client.domain.label.Label])
Delete the label.

Parameters **label** – label id or Label

find_label_by_id (label_id: str)
Retrieve the label by id.

Parameters **label_id** –

Returns Label

find_label_by_org (org_id) → List[influxdb_client.domain.label.Label]
Get the list of all labels for given organization.

Parameters **org_id** – organization id

Returns list of labels

find_labels () → List[influxdb_client.domain.label.Label]
Get all available labels.

Returns labels

update_label (label: influxdb_client.domain.label.Label)
Update an existing label name and properties.

Parameters **label** – label

Returns the updated label

2.6 OrganizationsApi

```
class influxdb_client.OrganizationsApi (influxdb_client)
    Implementation for '/api/v2/orgs' endpoint.

    Initialize defaults.

    create_organization (name: str = None, organization: influxdb_client.domain.organization.Organization = None) → influxdb_client.domain.organization.Organization
        Create an organization.

    delete_organization (org_id: str)
        Delete an organization.

    find_organization (org_id)
        Retrieve an organization.

    find_organizations ()
        List all organizations.

    me ()
        Return the current authenticated user.

class influxdb_client.domain.Organization (links=None, id=None, name=None, description=None, created_at=None, updated_at=None, status='active')
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Organization - a model defined in OpenAPI.

created_at
Get the created_at of this Organization.

Returns The created_at of this Organization.

Return type datetime

description
Get the description of this Organization.

Returns The description of this Organization.

Return type str

id
Get the id of this Organization.

Returns The id of this Organization.

Return type str

links
Get the links of this Organization.

Returns The links of this Organization.

Return type OrganizationLinks

name
Get the name of this Organization.

Returns The name of this Organization.

Return type `str`

status

Get the status of this Organization.

If inactive the organization is inactive.

Returns The status of this Organization.

Return type `str`

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

updated_at

Get the updated_at of this Organization.

Returns The updated_at of this Organization.

Return type `datetime`

2.7 UsersApi

class `influxdb_client.UsersApi` (`influxdb_client`)

Implementation for '/api/v2/users' endpoint.

Initialize defaults.

create_user (`name: str`) → `influxdb_client.domain.user.User`

Create a user.

me () → `influxdb_client.domain.user.User`

Return the current authenticated user.

class `influxdb_client.domain.User` (`id=None`, `oauth_id=None`, `name=None`, `status='active'`,
`links=None`)

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

User - a model defined in OpenAPI.

id

Get the id of this User.

Returns The id of this User.

Return type `str`

links

Get the links of this User.

Returns The links of this User.

Return type `UserLinks`

name
Get the name of this User.
Returns The name of this User.
Return type `str`

oauth_id
Get the oauth_id of this User.
Returns The oauth_id of this User.
Return type `str`

status
Get the status of this User.
If inactive the user is inactive.
Returns The status of this User.
Return type `str`

to_dict()
Return the model properties as a dict.

to_str()
Return the string representation of the model.

2.8 TasksApi

class `influxdb_client.TasksApi` (`influxdb_client`)
Implementation for '/api/v2/tasks' endpoint.

Initialize defaults.

add_label (`label_id: str, task_id: str`) → `influxdb_client.domain.label_response.LabelResponse`
Add a label to a task.

add_member (`member_id, task_id`)
Add a member to a task.

add_owner (`owner_id, task_id`)
Add an owner to a task.

cancel_run (`task_id: str, run_id: str`)
Cancel a currently running run.

Parameters

- **task_id** –
- **run_id** –

clone_task (`task: influxdb_client.domain.task.Task`) → `influxdb_client.domain.task.Task`
Clone a task.

create_task (`task: influxdb_client.domain.task.Task = None, task_create_request: influxdb_client.domain.task_create_request.TaskCreateRequest = None`) → `influxdb_client.domain.task.Task`
Create a new task.

create_task_cron (*name: str, flux: str, cron: str, org_id: str*) → influxdb_client.domain.task.Task

Create a new task with cron repetition schedule.

create_task_every (*name, flux, every, organization*) → influxdb_client.domain.task.Task

Create a new task with every repetition schedule.

delete_label (*label_id: str, task_id: str*)

Delete a label from a task.

delete_member (*member_id, task_id*)

Remove a member from a task.

delete_owner (*owner_id, task_id*)

Remove an owner from a task.

delete_task (*task_id: str*)

Delete a task.

find_task_by_id (*task_id*) → influxdb_client.domain.task.Task

Retrieve a task.

find_tasks (***kwargs*)

List all tasks.

Parameters

- **name** (*str*) – only returns tasks with the specified name
- **after** (*str*) – returns tasks after specified ID
- **user** (*str*) – filter tasks to a specific user ID
- **org** (*str*) – filter tasks to a specific organization name
- **org_id** (*str*) – filter tasks to a specific organization ID
- **limit** (*int*) – the number of tasks to return

Returns Tasks

find_tasks_by_user (*task_user_id*)

List all tasks by user.

get_labels (*task_id*)

List all labels for a task.

get_logs (*task_id: str*) → List[influxdb_client.domain.log_event.LogEvent]

Retrieve all logs for a task.

Parameters task_id – task id

get_members (*task_id: str*)

List all task members.

get_owners (*task_id*)

List all owners of a task.

get_run (*task_id: str, run_id: str*) → influxdb_client.domain.run.Run

Get run record for specific task and run id.

Parameters

- **task_id** – task id
- **run_id** – run id

Returns Run for specified task and run id

get_run_logs (*task_id: str, run_id: str*) → List[influxdb_client.domain.log_event.LogEvent]
Retrieve all logs for a run.

get_runs (*task_id, **kwargs*) → List[influxdb_client.domain.run.Run]
Retrieve list of run records for a task.

Parameters

- **task_id** – task id
- **after** (*str*) – returns runs after specified ID
- **limit** (*int*) – the number of runs to return
- **after_time** (*datetime*) – filter runs to those scheduled after this time, RFC3339
- **before_time** (*datetime*) – filter runs to those scheduled before this time, RFC3339

retry_run (*task_id: str, run_id: str*)
Retry a task run.

Parameters

- **task_id** – task id
- **run_id** – run id

run_manually (*task_id: str, scheduled_for: <module 'datetime' from
'/home/docs/.pyenv/versions/3.6.12/lib/python3.6/datetime.py'> = None*)
Manually start a run of the task now overriding the current schedule.

Parameters

- **task_id** –
- **scheduled_for** – planned execution

update_task (*task: influxdb_client.domain.task.Task*) → influxdb_client.domain.task.Task
Update a task.

update_task_request (*task_id, task_update_request: influxdb_client.domain.task_update_request.TaskUpdateRequest*)
→ influxdb_client.domain.task.Task
Update a task.

```
class influxdb_client.domain.Task (id=None, type=None, org_id=None, org=None,
                                   name=None, description=None, status=None, labels=None,
                                   authorization_id=None, flux=None, every=None,
                                   cron=None, offset=None, last_completed=None,
                                   last_run_status=None, last_run_error=None,
                                   created_at=None, updated_at=None, links=None)
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Task - a model defined in OpenAPI.

authorization_id

Get the authorization_id of this Task.

The ID of the authorization used when this task communicates with the query engine.

Returns The authorization_id of this Task.

Return type *str*

created_at

Get the created_at of this Task.

Returns The created_at of this Task.

Return type datetime

cron

Get the cron of this Task.

A task repetition schedule in the form ‘* * * * * *’; parsed from Flux.

Returns The cron of this Task.

Return type str

description

Get the description of this Task.

An optional description of the task.

Returns The description of this Task.

Return type str

every

Get the every of this Task.

A simple task repetition schedule; parsed from Flux.

Returns The every of this Task.

Return type str

flux

Get the flux of this Task.

The Flux script to run for this task.

Returns The flux of this Task.

Return type str

id

Get the id of this Task.

Returns The id of this Task.

Return type str

labels

Get the labels of this Task.

Returns The labels of this Task.

Return type list[Label]

last_run_error

Get the last_run_error of this Task.

Returns The last_run_error of this Task.

Return type str

last_run_status

Get the last_run_status of this Task.

Returns The last_run_status of this Task.

Return type `str`

latest_completed

Get the latest_completed of this Task.

Timestamp of latest scheduled, completed run, RFC3339.

Returns The latest_completed of this Task.

Return type `datetime`

links

Get the links of this Task.

Returns The links of this Task.

Return type `TaskLinks`

name

Get the name of this Task.

The name of the task.

Returns The name of this Task.

Return type `str`

offset

Get the offset of this Task.

Duration to delay after the schedule, before executing the task; parsed from flux, if set to zero it will remove this option and use 0 as the default.

Returns The offset of this Task.

Return type `str`

org

Get the org of this Task.

The name of the organization that owns this Task.

Returns The org of this Task.

Return type `str`

org_id

Get the org_id of this Task.

The ID of the organization that owns this Task.

Returns The org_id of this Task.

Return type `str`

status

Get the status of this Task.

Returns The status of this Task.

Return type `TaskStatusType`

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

type

Get the type of this Task.

The type of task, this can be used for filtering tasks on list actions.

Returns The type of this Task.

Return type `str`

updated_at

Get the updated_at of this Task.

Returns The updated_at of this Task.

Return type `datetime`

2.9 DeleteApi

class `influxdb_client.DeleteApi` (*influxdb_client*)

Implementation for '/api/v2/delete' endpoint.

Initialize defaults.

delete (*start: <module 'datetime' from '/home/docs/.pyenv/versions/3.6.12/lib/python3.6/datetime.py'>, stop: object, predicate: object, bucket: str, org: str*) → None
Delete Time series data from InfluxDB.

Parameters

- **start** – start time
- **stop** – stop time
- **predicate** – predicate
- **bucket** – bucket id or name from which data will be deleted
- **org** – organization id or name

Returns

class `influxdb_client.domain.DeletePredicateRequest` (*start=None, stop=None, predicate=None*)

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

DeletePredicateRequest - a model defined in OpenAPI.

predicate

Get the predicate of this DeletePredicateRequest.

InfluxQL-like delete statement

Returns The predicate of this DeletePredicateRequest.

Return type `str`

start

Get the start of this DeletePredicateRequest.

RFC3339Nano

Returns The start of this DeletePredicateRequest.

Return type datetime

stop

Get the stop of this DeletePredicateRequest.

RFC3339Nano

Returns The stop of this DeletePredicateRequest.

Return type datetime

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

InfluxDB 2.0 python client library.

Note: Use this client library with InfluxDB 2.x and InfluxDB 1.8+. For connecting to InfluxDB 1.7 or earlier instances, use the [influxdb-python](#) client library.

InfluxDB 2.0 client features

- **Querying data**
 - using the Flux language
 - into csv, raw data, `flux_table` structure, Pandas `DataFrame`
 - *How to queries*
- **Writing data using**
 - Line Protocol
 - Data Point
 - RxPY Observable
 - Pandas `DataFrame`
 - *How to writes*
- **InfluxDB 2.0 API client for management**
 - the client is generated from the `swagger` by using the `openapi-generator`
 - organizations & users management
 - buckets management
 - tasks management
 - authorizations
 - health check
 - ...
- **‘InfluxDB 1.8 API compatibility’_**
- **Examples**
 - **‘Connect to InfluxDB Cloud’_**
 - **‘How to efficiently import large dataset’_**

- ‘Efficiency write data from IOT sensor’_
 - ‘How to use Jupyter + Pandas + InfluxDB 2’_
- **Advanced Usage**
 - ‘Gzip support’_
 - ‘Delete data’_

CHAPTER 4

Installation

InfluxDB python library uses [RxPY](#) - The Reactive Extensions for Python (RxPY).

Python 3.6 or later is required.

Note: It is recommended to use `ciso8601` with `client` for parsing dates. `ciso8601` is much faster than built-in Python `datetime`. Since it's written as a C module the best way is build it from sources:

Windows:

You have to install [Visual C++ Build Tools 2015](#) to build `ciso8601` by `pip`.

conda:

Install from sources: `conda install -c conda-forge/label/cf202003 ciso8601`.

4.1 pip install

The python package is hosted on [PyPI](#), you can install latest version directly:

```
pip install influxdb-client[ciso]
```

Then import the package:

```
import influxdb_client
```

4.2 Setuptools

Install via [Setuptools](#).

```
python setup.py install --user
```

(or `sudo python setup.py install` to install the package for all users)

CHAPTER 5

Getting Started

Please follow the *Installation* and then run the following:

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, record=p)

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print(row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1
```


6.1 Via File

A client can be configured via *.ini file in segment influx2.

The following options are supported:

- `url` - the url to connect to InfluxDB
- `org` - default destination organization for writes and queries
- `token` - the token to use for the authorization
- `timeout` - socket timeout in ms (default value is 10000)
- `verify_ssl` - set this to false to skip verifying SSL certificate when calling API from https server
- `ssl_ca_cert` - set this to customize the certificate file to verify the peer

```
self.client = InfluxDBClient.from_config_file("config.ini")
```

6.2 Via Environment Properties

A client can be configured via environment properties.

Supported properties are:

- `INFLUXDB_V2_URL` - the url to connect to InfluxDB
- `INFLUXDB_V2_ORG` - default destination organization for writes and queries
- `INFLUXDB_V2_TOKEN` - the token to use for the authorization
- `INFLUXDB_V2_TIMEOUT` - socket timeout in ms (default value is 10000)
- `INFLUXDB_V2_VERIFY_SSL` - set this to false to skip verifying SSL certificate when calling API from https server

- INFLUXDB_V2_SSL_CA_CERT - set this to customize the certificate file to verify the peer

```
self.client = InfluxDBClient.from_env_properties()
```

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`

A

add_label() (*influxdb_client.TasksApi method*), 23
 add_member() (*influxdb_client.TasksApi method*), 23
 add_owner() (*influxdb_client.TasksApi method*), 23
 authorization_id (*influxdb_client.domain.Task attribute*), 25
 authorizations_api() (*influxdb_client.InfluxDBClient method*), 14

B

Bucket (*class in influxdb_client.domain*), 18
 buckets_api() (*influxdb_client.InfluxDBClient method*), 14
 BucketsApi (*class in influxdb_client*), 17

C

cancel_run() (*influxdb_client.TasksApi method*), 23
 clone_label() (*influxdb_client.LabelsApi method*), 20
 clone_task() (*influxdb_client.TasksApi method*), 23
 close() (*influxdb_client.InfluxDBClient method*), 14
 close() (*influxdb_client.WriteApi method*), 17
 create_bucket() (*influxdb_client.BucketsApi method*), 17
 create_label() (*influxdb_client.LabelsApi method*), 20
 create_organization() (*influxdb_client.OrganizationsApi method*), 21
 create_task() (*influxdb_client.TasksApi method*), 23
 create_task_cron() (*influxdb_client.TasksApi method*), 23
 create_task_every() (*influxdb_client.TasksApi method*), 24
 create_user() (*influxdb_client.UsersApi method*), 22
 created_at (*influxdb_client.domain.Bucket attribute*), 18

created_at (*influxdb_client.domain.Organization attribute*), 21
 created_at (*influxdb_client.domain.Task attribute*), 25
 cron (*influxdb_client.domain.Task attribute*), 26

D

delete() (*influxdb_client.DeleteApi method*), 28
 delete_api() (*influxdb_client.InfluxDBClient method*), 14
 delete_bucket() (*influxdb_client.BucketsApi method*), 18
 delete_label() (*influxdb_client.LabelsApi method*), 20
 delete_label() (*influxdb_client.TasksApi method*), 24
 delete_member() (*influxdb_client.TasksApi method*), 24
 delete_organization() (*influxdb_client.OrganizationsApi method*), 21
 delete_owner() (*influxdb_client.TasksApi method*), 24
 delete_task() (*influxdb_client.TasksApi method*), 24
 DeleteApi (*class in influxdb_client*), 28
 DeletePredicateRequest (*class in influxdb_client.domain*), 28
 description (*influxdb_client.domain.Bucket attribute*), 18
 description (*influxdb_client.domain.Organization attribute*), 21
 description (*influxdb_client.domain.Task attribute*), 26

E

every (*influxdb_client.domain.Task attribute*), 26

F

find_bucket_by_id() (*influxdb_client.BucketsApi*

method), 18
 find_bucket_by_name() (influxdb_client.BucketsApi method), 18
 find_buckets() (influxdb_client.BucketsApi method), 18
 find_label_by_id() (influxdb_client.LabelsApi method), 20
 find_label_by_org() (influxdb_client.LabelsApi method), 20
 find_labels() (influxdb_client.LabelsApi method), 20
 find_organization() (influxdb_client.OrganizationsApi method), 21
 find_organizations() (influxdb_client.OrganizationsApi method), 21
 find_task_by_id() (influxdb_client.TasksApi method), 24
 find_tasks() (influxdb_client.TasksApi method), 24
 find_tasks_by_user() (influxdb_client.TasksApi method), 24
 flush() (influxdb_client.WriteApi method), 17
 flux (influxdb_client.domain.Task attribute), 26
 from_config_file() (influxdb_client.InfluxDBClient class method), 14
 from_env_properties() (influxdb_client.InfluxDBClient class method), 14

G

get_labels() (influxdb_client.TasksApi method), 24
 get_logs() (influxdb_client.TasksApi method), 24
 get_members() (influxdb_client.TasksApi method), 24
 get_owners() (influxdb_client.TasksApi method), 24
 get_run() (influxdb_client.TasksApi method), 24
 get_run_logs() (influxdb_client.TasksApi method), 24
 get_runs() (influxdb_client.TasksApi method), 25

H

health() (influxdb_client.InfluxDBClient method), 15

I

id (influxdb_client.domain.Bucket attribute), 18
 id (influxdb_client.domain.Organization attribute), 21
 id (influxdb_client.domain.Task attribute), 26
 id (influxdb_client.domain.User attribute), 22
 InfluxDBClient (class in influxdb_client), 13

L

labels (influxdb_client.domain.Bucket attribute), 19

labels (influxdb_client.domain.Task attribute), 26
 labels_api() (influxdb_client.InfluxDBClient method), 15
 LabelsApi (class in influxdb_client), 20
 last_run_error (influxdb_client.domain.Task attribute), 26
 last_run_status (influxdb_client.domain.Task attribute), 26
 latest_completed (influxdb_client.domain.Task attribute), 27
 links (influxdb_client.domain.Bucket attribute), 19
 links (influxdb_client.domain.Organization attribute), 21
 links (influxdb_client.domain.Task attribute), 27
 links (influxdb_client.domain.User attribute), 22

M

me() (influxdb_client.OrganizationsApi method), 21
 me() (influxdb_client.UsersApi method), 22

N

name (influxdb_client.domain.Bucket attribute), 19
 name (influxdb_client.domain.Organization attribute), 21
 name (influxdb_client.domain.Task attribute), 27
 name (influxdb_client.domain.User attribute), 22

O

oauth_id (influxdb_client.domain.User attribute), 23
 offset (influxdb_client.domain.Task attribute), 27
 org (influxdb_client.domain.Task attribute), 27
 org_id (influxdb_client.domain.Bucket attribute), 19
 org_id (influxdb_client.domain.Task attribute), 27
 Organization (class in influxdb_client.domain), 21
 organizations_api() (influxdb_client.InfluxDBClient method), 15
 OrganizationsApi (class in influxdb_client), 21

P

predicate (influxdb_client.domain.DeletePredicateRequest attribute), 28

Q

query() (influxdb_client.QueryApi method), 15
 query_api() (influxdb_client.InfluxDBClient method), 15
 query_csv() (influxdb_client.QueryApi method), 16
 query_data_frame() (influxdb_client.QueryApi method), 16
 query_data_frame_stream() (influxdb_client.QueryApi method), 16
 query_raw() (influxdb_client.QueryApi method), 16
 query_stream() (influxdb_client.QueryApi method), 16

QueryApi (class in influxdb_client), 15

R

ready() (influxdb_client.InfluxDBClient method), 15
 retention_rules (influxdb_client.domain.Bucket attribute), 19
 retry_run() (influxdb_client.TasksApi method), 25
 rp (influxdb_client.domain.Bucket attribute), 19
 run_manually() (influxdb_client.TasksApi method), 25

S

start (influxdb_client.domain.DeletePredicateRequest attribute), 28
 status (influxdb_client.domain.Organization attribute), 22
 status (influxdb_client.domain.Task attribute), 27
 status (influxdb_client.domain.User attribute), 23
 stop (influxdb_client.domain.DeletePredicateRequest attribute), 29

T

Task (class in influxdb_client.domain), 25
 tasks_api() (influxdb_client.InfluxDBClient method), 15
 TasksApi (class in influxdb_client), 23
 to_dict() (influxdb_client.domain.Bucket method), 19
 to_dict() (influxdb_client.domain.DeletePredicateRequest method), 29
 to_dict() (influxdb_client.domain.Organization method), 22
 to_dict() (influxdb_client.domain.Task method), 27
 to_dict() (influxdb_client.domain.User method), 23
 to_str() (influxdb_client.domain.Bucket method), 19
 to_str() (influxdb_client.domain.DeletePredicateRequest method), 29
 to_str() (influxdb_client.domain.Organization method), 22
 to_str() (influxdb_client.domain.Task method), 27
 to_str() (influxdb_client.domain.User method), 23
 type (influxdb_client.domain.Bucket attribute), 19
 type (influxdb_client.domain.Task attribute), 27

U

update_label() (influxdb_client.LabelsApi method), 20
 update_task() (influxdb_client.TasksApi method), 25
 update_task_request() (influxdb_client.TasksApi method), 25
 updated_at (influxdb_client.domain.Bucket attribute), 19

updated_at (influxdb_client.domain.Organization attribute), 22
 updated_at (influxdb_client.domain.Task attribute), 28
 User (class in influxdb_client.domain), 22
 users_api() (influxdb_client.InfluxDBClient method), 15
 UsersApi (class in influxdb_client), 22

W

write() (influxdb_client.WriteApi method), 17
 write_api() (influxdb_client.InfluxDBClient method), 15
 WriteApi (class in influxdb_client), 17