
influxdb*client*

Release 1.16.0

Apr 01, 2021

Contents:

| | | |
|----------|--|-----------|
| 1 | User Guide | 1 |
| 1.1 | Query | 2 |
| 1.2 | Pandas DataFrame | 2 |
| 1.3 | Write | 3 |
| 1.3.1 | The data could be written as | 3 |
| 1.3.2 | Batching | 3 |
| 1.3.3 | Default Tags | 6 |
| 1.3.4 | Asynchronous client | 6 |
| 1.3.5 | Synchronous client | 7 |
| 1.4 | Delete data | 7 |
| 1.5 | Gzip support | 8 |
| 1.6 | Debugging | 8 |
| 1.7 | Examples | 8 |
| 1.7.1 | How to efficiently import large dataset | 8 |
| 1.7.2 | Efficiency write data from IOT sensor | 10 |
| 1.7.3 | Connect to InfluxDB Cloud | 12 |
| 1.7.4 | How to use Jupyter + Pandas + InfluxDB 2 | 13 |
| 1.7.5 | Other examples | 14 |
| 2 | API Reference | 15 |
| 2.1 | InfluxDBClient | 15 |
| 2.2 | QueryApi | 18 |
| 2.3 | WriteApi | 19 |
| 2.4 | BucketsApi | 20 |
| 2.5 | LabelsApi | 22 |
| 2.6 | OrganizationsApi | 23 |
| 2.7 | UsersApi | 25 |
| 2.8 | TasksApi | 26 |
| 2.9 | DeleteApi | 31 |
| 3 | InfluxDB 2.0 client features | 33 |
| 4 | Installation | 35 |
| 4.1 | pip install | 35 |
| 4.2 | Setuptools | 35 |
| 5 | Getting Started | 37 |

| | |
|--|-----------|
| 6 Client configuration | 39 |
| 6.1 Via File | 39 |
| 6.2 Via Environment Properties | 39 |
| 7 Indices and tables | 41 |
| Index | 43 |

CHAPTER 1

User Guide

- *Query*
- *Pandas DataFrame*
- *Write*
 - *The data could be written as*
 - *Batching*
 - *Default Tags*
 - * *Via API*
 - * *Via Configuration file*
 - * *Via Environment Properties*
 - *Asynchronous client*
 - *Synchronous client*
- *Delete data*
- *Gzip support*
- *Debugging*
- *Examples*
 - *How to efficiently import large dataset*
 - *Efficiency write data from IOT sensor*
 - *Connect to InfluxDB Cloud*
 - *How to use Jupyter + Pandas + InfluxDB 2*
 - *Other examples*

1.1 Query

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, record=p)

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print (row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1
```

1.2 Pandas DataFrame

Note: For DataFrame querying you should install Pandas dependency via pip install influxdb-client[extra].

Note: Note that if a query returns more then one table then the client generates a DataFrame for each of them.

The client is able to retrieve data in **Pandas DataFrame** format thought `query_data_frame`:

```
from influxdb_client import InfluxDBClient, Point, Dialect
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

"""

Prepare data
```

(continues on next page)

(continued from previous page)

```

"""
_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
    ↪3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

"""
Query: using Pandas DataFrame
"""
data_frame = query_api.query_data_frame('from(bucket:"my-bucket") '
                                         '|> range(start: -10m) '
                                         '|> pivot(rowKey:["_time"], columnKey: ["
    ↪field"], valueColumn: "_value") '
                                         '|> keep(columns: ["location", "temperature"])
    ↪')
print(data_frame.to_string())

"""
Close client
"""
client.close()

```

Output:

1.3 Write

The WriteApi supports synchronous, asynchronous and batching writes into InfluxDB 2.0. The data should be passed as a [InfluxDB Line Protocol](#), [Data Point](#) or Observable stream.

Important: The WriteApi in batching mode (default mode) is suppose to run as a singleton. To flush all your data you should call “`_write_client.close()`“ at the end of your script.

The default instance of WriteApi use batching.

1.3.1 The data could be written as

1. string or bytes that is formatted as a InfluxDB’s line protocol
2. [Data Point](#) structure
3. Dictionary style mapping with keys: measurement, tags, fields and time
4. List of above items
5. A batching type of write also supports an Observable that produce one of an above item
6. [Pandas DataFrame](#)

1.3.2 Batching

The batching is configurable by `write_options`:

| Property | Description | Default Value |
|-------------------------------|---|---------------|
| <code>batch_size</code> | the number of data pointx to collect in a batch | 1000 |
| <code>flush_interval</code> | number of milliseconds before the batch is written | 1000 |
| <code>jitter_interval</code> | the number of milliseconds to increase the batch flush interval by a random amount | 0 |
| <code>retry_interval</code> | number of milliseconds to retry unsuccessful write. The retry interval is used when the InfluxDB server does not specify “Retry-After” header. | 5000 |
| <code>max_retries</code> | the number of max retries when write fails | 3 |
| <code>max_retry_delay</code> | maximum delay between each retry attempt in milliseconds | 180_000 |
| <code>exponential_base</code> | the base for the exponential retry delay, the next delay is computed as <code>retry_interval * exponential_base^(attempts-1) + random(jitter_interval)</code> | 5 |

```

from datetime import datetime, timedelta

import pandas as pd
import rx
from pytz import UTC
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions

_client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
_write_client = _client.write_api(write_options=WriteOptions(batch_size=500,
                                                               flush_interval=10_000,
                                                               jitter_interval=2_000,
                                                               retry_interval=5_000,
                                                               max_retries=5,
                                                               max_retry_delay=30_000,
                                                               exponential_base=2))

"""
Write Line Protocol formatted as string
"""
_write_client.write("my-bucket", "my-org", "h2o_feet,location=coyote_creek water_"
                    "level=1.0 1")
_write_client.write("my-bucket", "my-org", ["h2o_feet,location=coyote_creek water_"
                                             "level=2.0 2",
                                             "h2o_feet,location=coyote_creek water_"
                                             "level=3.0 3"])

"""
Write Line Protocol formatted as byte array
"""
_write_client.write("my-bucket", "my-org", "h2o_feet,location=coyote_creek water_"
                    "level=1.0 1".encode())
_write_client.write("my-bucket", "my-org", ["h2o_feet,location=coyote_creek water_"
                                             "level=2.0 2".encode(),
                                             "h2o_feet,location=coyote_creek water_"
                                             "level=3.0 3".encode()])

"""
Write Dictionary-style object
"""

```

(continues on next page)

(continued from previous page)

```

"""
_write_client.write("my-bucket", "my-org", {"measurement": "h2o_feet", "tags": {
    "location": "coyote_creek"}, "fields": {"water_level": 1.0}, "time": 1}
)
_write_client.write("my-bucket", "my-org", [{"measurement": "h2o_feet", "tags": {
    "location": "coyote_creek"}, "fields": {"water_level": 2.0}, "time": 2},
    {"measurement": "h2o_feet", "tags": {"location": "coyote_creek"}, "fields": {"water_level": 3.0}, "time": 3}])

"""
Write Data Point
"""
_write_client.write("my-bucket", "my-org",
    Point("h2o_feet").tag("location", "coyote_creek").field("water_level", 4.0).time(4))
_write_client.write("my-bucket", "my-org",
    [Point("h2o_feet").tag("location", "coyote_creek").field("water_level", 5.0).time(5),
     Point("h2o_feet").tag("location", "coyote_creek").field("water_level", 6.0).time(6)])

"""
Write Observable stream
"""
_data = rx \
    .range(7, 11) \
    .pipe(ops.map(lambda i: "h2o_feet", location=coyote_creek water_level={0}.0 {0}).
format(i))

_write_client.write("my-bucket", "my-org", _data)

"""
Write Pandas DataFrame
"""
_now = datetime.now(UTC)
_data_frame = pd.DataFrame(data=[[{"coyote_creek": 1.0}, {"coyote_creek": 2.0}], index=[_now, _now + timedelta(hours=1)], columns=[["location"], ["water_level"]])

_write_client.write("my-bucket", "my-org", record=_data_frame, data_frame_measurement_name='h2o_feet',
                    data_frame_tag_columns=['location'])

"""
Close client
"""
_write_client.close()
_client.close()

```

1.3.3 Default Tags

Sometimes it is useful to store same information in every measurement e.g. hostname, location, customer. The client is able to use static value or env property as a tag value.

The expressions:

- California Miner - static value
- \${env.hostname} - environment property

Via API

```
point_settings = PointSettings()
point_settings.add_default_tag("id", "132-987-655")
point_settings.add_default_tag("customer", "California Miner")
point_settings.add_default_tag("data_center", "${env.data_center}")

self.write_client = self.client.write_api(write_options=SYNCHRONOUS, point_
    ↪settings=point_settings)

self.write_client = self.client.write_api(write_options=SYNCHRONOUS,
                                         point_settings=PointSettings(**{
                                             "id": "132-987-655",
                                             "customer": "California Miner"
                                         }))
```

Via Configuration file

In a `ini` configuration file you are able to specify default tags by `tags` segment.

```
self.client = InfluxDBClient.from_config_file("config.ini")
```

You could also use a `TOML` format for the configuration file.

Via Environment Properties

You are able to specify default tags by environment properties with prefix `INFLUXDB_V2_TAG_`.

Examples:

- `INFLUXDB_V2_TAG_ID`
- `INFLUXDB_V2_TAG_HOSTNAME`

```
self.client = InfluxDBClient.from_env_properties()
```

1.3.4 Asynchronous client

Data are writes in an asynchronous HTTP request.

```

from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import ASYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
write_api = client.write_api(write_options=ASYNCHRONOUS)

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪3)

async_result = write_api.write(bucket="my-bucket", record=[_point1, _point2])
async_result.get()

client.close()

```

1.3.5 Synchronous client

Data are writes in a synchronous HTTP request.

```

from influxdb_client import InfluxDBClient, Point
from influxdb_client .client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")
write_api = client.write_api(write_options=SYNCHRONOUS)

_point1 = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)
_point2 = Point("my_measurement").tag("location", "New York").field("temperature", 24.
↪3)

write_api.write(bucket="my-bucket", record=[_point1, _point2])

client.close()

```

1.4 Delete data

The delete_api.py supports deletes points from an InfluxDB bucket.

```

from influxdb_client import InfluxDBClient

client = InfluxDBClient(url="http://localhost:8086", token="my-token")

delete_api = client.delete_api()

"""
Delete Data
"""
start = "1970-01-01T00:00:00Z"
stop = "2021-02-01T00:00:00Z"
delete_api.delete(start, stop, '_measurement="my_measurement"', bucket='my-bucket', ↴
↪org='my-org')

"""
Close client

```

(continues on next page)

(continued from previous page)

```
"""
client.close()
```

1.5 Gzip support

InfluxDBClient does not enable gzip compression for http requests by default. If you want to enable gzip to reduce transfer data's size, you can call:

```
from influxdb_client import InfluxDBClient

_db_client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org",
                           enable_gzip=True)
```

1.6 Debugging

For debug purpose you can enable verbose logging of http requests. Both request header and body will be logged to standard output.

```
_client = InfluxDBClient(url="http://localhost:8086", token="my-token", debug=True,
                           org="my-org")
```

1.7 Examples

1.7.1 How to efficiently import large dataset

The following example shows how to import dataset with dozen megabytes. If you would like to import gigabytes of data then use our multiprocessing example: `import_data_set_multiprocessing.py` for use a full capability of your hardware.

- sources - `import_data_set.py`

```
"""
Import VIX - CBOE Volatility Index - from "vix-daily.csv" file into InfluxDB 2.0

https://datahub.io/core/finance-vix#data
"""

from collections import OrderedDict
from csv import DictReader

import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions

def parse_row(row: OrderedDict):
    """Parse row of CSV file into Point with structure:
```

(continues on next page)

(continued from previous page)

```

financial-analysis,type=vix-daily close=18.47,high=19.82,low=18.28,open=19.82
↪11981952000000000000

CSV format:
Date,VIX Open,VIX High,VIX Low,VIX Close\n
2004-01-02,17.96,18.68,17.54,18.22\n
2004-01-05,18.45,18.49,17.44,17.49\n
2004-01-06,17.66,17.67,16.19,16.73\n
2004-01-07,16.72,16.75,15.5,15.5\n
2004-01-08,15.42,15.68,15.32,15.61\n
2004-01-09,16.15,16.88,15.57,16.75\n
...
...

:param row: the row of CSV file
:return: Parsed csv row to [Point]
"""

"""

For better performance is sometimes useful directly create a LineProtocol to
↪avoid unnecessary escaping overhead:
"""

# from pytz import UTC
# import ciso8601
# from influxdb_client.client.write.point import EPOCH
#
# time = (UTC.localize(ciso8601.parse_datetime(row["Date"])) - EPOCH).total_
↪seconds() * 1e9
# return f"financial-analysis,type=vix-daily" \
#         f" close={float(row['VIX Close'])},high={float(row['VIX High'])},low="
↪{float(row['VIX Low'])},open={float(row['VIX Open'])} " \
#         f" {int(time)}"

return Point("financial-analysis") \
    .tag("type", "vix-daily") \
    .field("open", float(row['VIX Open'])) \
    .field("high", float(row['VIX High'])) \
    .field("low", float(row['VIX Low'])) \
    .field("close", float(row['VIX Close'])) \
    .time(row['Date'])

"""

Converts vix-daily.csv into sequence of data point
"""

data = rx \
    .from_iterable(DictReader(open('vix-daily.csv', 'r'))) \
    .pipe(ops.map(lambda row: parse_row(row)))

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org",
↪debug=True)

"""

Create client that writes data in batches with 50_000 items.
"""

write_api = client.write_api(write_options=WriteOptions(batch_size=50_000, flush_
↪interval=10_000))

```

(continues on next page)

(continued from previous page)

```

"""
Write data into InfluxDB
"""

write_api.write(bucket="my-bucket", record=data)
write_api.close()

"""

Querying max value of CBOE Volatility Index
"""

query = 'from(bucket:"my-bucket")' \
    '|> range(start: 0, stop: now())' \
    '|> filter(fn: (r) => r._measurement == "financial-analysis")' \
    '|> max()
result = client.query_api().query(query=query)

"""

Processing results
"""

print()
print("== results ==")
print()
for table in result:
    for record in table.records:
        print('max {0:5} = {1}'.format(record.get_field(), record.get_value()))

"""

Close client
"""

client.close()

```

1.7.2 Efficiency write data from IOT sensor

- sources - iot_sensor.py

```

"""
Efficiency write data from IOT sensor - write changed temperature every minute
"""

import atexit
import platform
from datetime import timedelta

import psutil as psutil
import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, WriteApi, WriteOptions

def on_exit(db_client: InfluxDBClient, write_api: WriteApi):
    """Close clients after terminate a script.

    :param db_client: InfluxDB client
    :param write_api: WriteApi
    :return: nothing
    """
    write_api.close()

```

(continues on next page)

(continued from previous page)

```

    db_client.close()

def sensor_temperature():
    """Read a CPU temperature. The [psutil] doesn't support MacOS so we use [sysctl].
    :return: actual CPU temperature
    """
    os_name = platform.system()
    if os_name == 'Darwin':
        from subprocess import check_output
        output = check_output(["sysctl", "machdep.xcpm.cpu_thermal_level"])
        import re
        return re.findall(r'\d+', str(output))[0]
    else:
        return psutil.sensors_temperatures()["coretemp"][0]

def line_protocol(temperature):
    """Create a InfluxDB line protocol with structure:
    iot_sensor,hostname=mine_sensor_12,type=temperature value=68

    :param temperature: the sensor temperature
    :return: Line protocol to write into InfluxDB
    """
    import socket
    return 'iot_sensor,hostname={},type=temperature value={}'.format(socket.
    ↪gethostname(), temperature)

"""
Read temperature every minute; distinct_until_changed - produce only if temperature ↪
change
"""
data = rx\
    .interval(period=timedelta(seconds=60))\
    .pipe(ops.map(lambda t: sensor_temperature()),
          ops.distinct_until_changed(),
          ops.map(lambda temperature: line_protocol(temperature)))

_db_client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org ↪",
                            debug=True)

"""
Create client that writes data into InfluxDB
"""
_write_api = _db_client.write_api(write_options=WriteOptions(batch_size=1))
_write_api.write(bucket="my-bucket", record=data)

"""
Call after terminate a script
"""
atexit.register(on_exit, _db_client, _write_api)

```

(continues on next page)

(continued from previous page)

input()

1.7.3 Connect to InfluxDB Cloud

The following example demonstrate a simplest way how to write and query date with the InfluxDB Cloud.

At first point you should create an authentication token as is described [here](#).

After that you should configure properties: `influx_cloud_url`, `influx_cloud_token`, `bucket` and `org` in a `influx_cloud.py` example.

The last step is run a python script via: `python3 influx_cloud.py`.

- sources - `influx_cloud.py`

```
"""
Connect to InfluxDB 2.0 - write data and query them
"""

from datetime import datetime

from influxdb_client import Point, InfluxDBClient
from influxdb_client.client.write_api import SYNCHRONOUS

"""
Configure credentials
"""
influx_cloud_url = 'https://us-west-2-1.aws.cloud2.influxdata.com'
influx_cloud_token = '...'
bucket = '...'
org = '...'

client = InfluxDBClient(url=influx_cloud_url, token=influx_cloud_token)
try:
    kind = 'temperature'
    host = 'host1'
    device = 'opt-123'

    """
    Write data by Point structure
    """
    point = Point(kind).tag('host', host).tag('device', device).field('value', 25.3).
        time(datetime.utcnow())

    print(f'Writing to InfluxDB cloud: {point.to_line_protocol()} ...')

    write_api = client.write_api(write_options=SYNCHRONOUS)
    write_api.write(bucket=bucket, org=org, record=point)

    print()
    print('success')
    print()
    print()

    """
    Query written data
    """

```

(continues on next page)

(continued from previous page)

```

"""
query = f'from(bucket: "{bucket}") |> range(start: -1d) |> filter(fn: (r) => r._
˓→measurement == "{kind}")'
print(f'Querying from InfluxDB cloud: "{query}" ...')
print()

query_api = client.query_api()
tables = query_api.query(query=query, org=org)

for table in tables:
    for row in table.records:
        print(f'{row.values["_time"]}: host={row.values["host"]}, device={row.
˓→values["device"]}'
              f'{row.values["_value"]} °C')

    print()
print('success')

except Exception as e:
    print(e)
finally:
    client.close()

```


1.7.4 How to use Jupyter + Pandas + InfluxDB 2

The first example shows how to use client capabilities to predict stock price via Keras, TensorFlow, sklearn:

The example is taken from [Kaggle](#).

- sources - stock-predictions.ipynb

Result:



The second example shows how to use client capabilities to realtime visualization via `hvPlot`, `Streamz`, `RxPY`:

- sources - `realtime-stream.ipynb`

1.7.5 Other examples

You could find all examples at GitHub: [influxdb-client-python/examples](https://github.com/influxdb-client/python/examples).

CHAPTER 2

API Reference

- *InfluxDBClient*
- *QueryApi*
- *WriteApi*
- *BucketsApi*
- *LabelsApi*
- *OrganizationsApi*
- *UsersApi*
- *TasksApi*
- *DeleteApi*

2.1 InfluxDBClient

```
class influxdb_client.InfluxDBClient(url, token, debug=None, timeout=10000, enable_gzip=False, org: str = None, default_tags: dict = None, **kwargs)
```

InfluxDBClient is client for InfluxDB v2.

Initialize defaults.

Parameters

- **url** – InfluxDB server API url (ex. `http://localhost:8086`).
- **token** – auth token
- **debug** – enable verbose logging of http requests

- **timeout** – default http client timeout
- **enable_gzip** – Enable Gzip compression for http requests. Currently only the “Write” and “Query” endpoints supports the Gzip compression.
- **org** – organization name (used as a default in query and write API)

Key bool verify_ssl Set this to false to skip verifying SSL certificate when calling API from https server.

Key str ssl_ca_cert Set this to customize the certificate file to verify the peer.

Key str proxy Set this to configure the http proxy to be used (ex. <http://localhost:3128>)

Key int connection_pool_maxsize Number of connections to save that can be reused by urllib3.
Defaults to “multiprocessing.cpu_count() * 5”.

Key urllib3.util.retry.Retry retries Set the default retry strategy that is used for all HTTP requests except batching writes. As a default there is no one retry strategy.

authorizations_api() → influxdb_client.client.AuthorizationsApi
Create the Authorizations API instance.

Returns authorizations api

buckets_api() → influxdb_client.client.BucketsApi
Create the Bucket API instance.

Returns buckets api

close()
Shutdown the client.

delete_api() → influxdb_client.client.DeleteApi
Get the delete metrics API instance.

Returns delete api

classmethod from_config_file(config_file: str = 'config.ini', debug=None, enable_gzip=False)
Configure client via configuration file. The configuration has to be under ‘influx’ section.

The supported formats:

- <https://docs.python.org/3/library/configparser.html>
- <https://toml.io/en/>

Configuration options:

- url
- org
- token
- timeout,
- verify_ssl
- ssl_ca_cert
- connection_pool_maxsize

config.ini example:

```
[influx2]
url=http://localhost:8086
org=my-org
token=my-token
timeout=6000
connection_pool_maxsize=25

[tags]
id = 132-987-655
customer = California Miner
data_center = ${env.data_center}
```

config.toml example:

```
[influx2]
url = "http://localhost:8086"
token = "my-token"
org = "my-org"
timeout = 6000
connection_pool_maxsize = 25

[tags]
id = "132-987-655"
customer = "California Miner"
data_center = "${env.data_center}"
```

classmethod from_env_properties (debug=None, enable_gzip=False)

Configure client via environment properties.

Supported environment properties:

- INFLUXDB_V2_URL
- INFLUXDB_V2_ORG
- INFLUXDB_V2_TOKEN
- INFLUXDB_V2_TIMEOUT
- INFLUXDB_V2_VERIFY_SSL
- INFLUXDB_V2_SSL_CA_CERT
- INFLUXDB_V2_CONNECTION_POOL_MAXSIZE

health () → influxdb_client.domain.health_check.HealthCheck

Get the health of an instance.

Returns HealthCheck

labels_api () → influxdb_client.client.labels_api.LabelsApi

Create the Labels API instance.

Returns labels api

organizations_api () → influxdb_client.client.organizations_api.OrganizationsApi

Create the Organizations API instance.

Returns organizations api

query_api () → influxdb_client.client.query_api.QueryApi

Create a Query API instance.

Returns Query api instance

ready() → influxdb_client.domain.ready.Ready
Get The readiness of the InfluxDB 2.0.

Returns Ready

tasks_api() → influxdb_client.client.tasks_api.TasksApi
Create the Tasks API instance.

Returns tasks api

users_api() → influxdb_client.client.users_api.UsersApi
Create the Users API instance.

Returns users api

write_api (`write_options=<influxdb_client.client.write_api.WriteOptions object>, point_settings=<influxdb_client.client.write_api.PointSettings object>)` → `influxdb_client.client.write_api.WriteApi`
Create a Write API instance.

Parameters

- **point_settings** –
 - **write_options** – write api configuration

Returns write api instance

2.2 QueryApi

```
class influxdb_client.QueryApi(influxdb_client)
```

Implementation for '/api/v2/query' endpoint.

Initialize query client.

Parameters `influxdb_client` – influxdb client

query (*query: str, org=None*) → List[influxdb_client.client.flux_table.FluxTable]

Execute synchronous Flux query and return result as a List[‘FluxTable’].

Parameters

- **query** – the Flux query
 - **org** – organization name (optional if already specified in InfluxDBClient)

Returns

```
query_csv(query: str, org=None, dialect: influxdb_client.domain.dialect.Dialect = {'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True})
```

Execute the Flux query and return results as a CSV iterator. Each iteration returns a row of the CSV file.

Parameters

- **query** – a Flux query
 - **org** – organization name (optional if already specified in InfluxDBClient)
 - **dialect** – csv dialect format

Returns The returned object is an iterator. Each iteration returns a row of the CSV file (which can span multiple input lines).

query_data_frame (*query: str, org=None, data_frame_index: List[str] = None*)

Execute synchronous Flux query and return Pandas DataFrame.

Note that if a query returns more then one table than the client generates a DataFrame for each of them.

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **data_frame_index** – the list of columns that are used as DataFrame index

Returns**query_data_frame_stream** (*query: str, org=None, data_frame_index: List[str] = None*)

Execute synchronous Flux query and return stream of Pandas DataFrame as a Generator[‘pd.DataFrame’].

Note that if a query returns more then one table than the client generates a DataFrame for each of them.

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **data_frame_index** – the list of columns that are used as DataFrame index

Returns**query_raw** (*query: str, org=None, dialect={'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True}*)

Execute synchronous Flux query and return result as raw unprocessed result as a str.

Parameters

- **query** – a Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns str**query_stream** (*query: str, org=None*) → Generator[[*influxdb_client.client.flux_table.FluxRecord, Any, None*]]

Execute synchronous Flux query and return stream of FluxRecord as a Generator[‘FluxRecord’].

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)

Returns

2.3 WriteApi

```
class influxdb_client.WriteApi (influxdb_client, write_options: influxdb_client.client.write_api.WriteOptions = <influxdb_client.client.write_api.WriteOptions object>, point_settings: influxdb_client.client.write_api.PointSettings = <influxdb_client.client.write_api.PointSettings object>)
```

Implementation for ‘/api/v2/write’ endpoint.

Initialize defaults.

close()

Flush data and dispose a batching buffer.

flush()

Flush data.

write(*bucket*: str, *org*: str = None, *record*: Union[str, Iterable[str], influxdb_client.client.write.point.Point, Iterable[Point], dict, Iterable[dict], bytes, Iterable[bytes], rx.core.observable.observable.Observable] = None, *write_precision*: influxdb_client.domain.write_precision.WritePrecision = 'ns', **kwargs) → Any
Write time-series data into InfluxDB.

Parameters

- **org** (*str*) – specifies the destination organization for writes; take either the ID or Name interchangeably; if both orgID and org are specified, org takes precedence. (required)
- **bucket** (*str*) – specifies the destination bucket for writes (required)
- **write_precision** (*WritePrecision*) – specifies the precision for the unix timestamps within the body line-protocol. The precision specified on a Point has precedes and is used for write.
- **record** – Points, line protocol, Pandas DataFrame, RxPY Observable to write

Key data_frame_measurement_name name of measurement for writing Pandas DataFrame

Key data_frame_tag_columns list of DataFrame columns which are tags, rest columns will be fields

2.4 BucketsApi

class influxdb_client.BucketsApi(*influxdb_client*)

Implementation for '/api/v2/buckets' endpoint.

Initialize defaults.

create_bucket(*bucket*=None, *bucket_name*=None, *org_id*=None, *retention_rules*=None, *description*=None) → influxdb_client.domain.bucket.Bucket
Create a bucket.

Parameters

- **bucket** (*Bucket*) – bucket to create (required)
- **bucket_name** – bucket name
- **description** – bucket description
- **org_id** – org_id
- **bucket_name** – bucket name
- **retention_rules** – retention rules array or single BucketRetentionRules

Returns Bucket If the method is called asynchronously, returns the request thread.

delete_bucket(*bucket*)

Delete a bucket.

Parameters **bucket** – bucket id or Bucket

Returns Bucket If the method is called asynchronously, returns the request thread.

find_bucket_by_id(*id*)
Find bucket by ID.

Parameters *id* –

Returns

find_bucket_by_name(*bucket_name*)
Find bucket by name.

Parameters *bucket_name* – bucket name

Returns Bucket

find_buckets()
Get all buckets.

```
class influxdb_client.domain.Bucket(links=None, id=None, type='user', name=None,
                                    description=None, org_id=None, rp=None,
                                    created_at=None, updated_at=None, retention_rules=None, labels=None)
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Bucket - a model defined in OpenAPI.

created_at

Get the created_at of this Bucket.

Returns The created_at of this Bucket.

Return type datetime

description

Get the description of this Bucket.

Returns The description of this Bucket.

Return type str

id

Get the id of this Bucket.

Returns The id of this Bucket.

Return type str

labels

Get the labels of this Bucket.

Returns The labels of this Bucket.

Return type list[Label]

links

Get the links of this Bucket.

Returns The links of this Bucket.

Return type BucketLinks

name

Get the name of this Bucket.

Returns The name of this Bucket.

Return type str

org_id

Get the org_id of this Bucket.

Returns The org_id of this Bucket.

Return type str

retention_rules

Get the retention_rules of this Bucket.

Rules to expire or retain data. No rules means data never expires.

Returns The retention_rules of this Bucket.

Return type list[BucketRetentionRules]

rp

Get the rp of this Bucket.

Returns The rp of this Bucket.

Return type str

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

type

Get the type of this Bucket.

Returns The type of this Bucket.

Return type str

updated_at

Get the updated_at of this Bucket.

Returns The updated_at of this Bucket.

Return type datetime

2.5 LabelsApi

```
class influxdb_client.LabelsApi(influxdb_client)
```

Implementation for '/api/v2/labels' endpoint.

Initialize defaults.

```
clone_label(cloned_name: str, label: influxdb_client.domain.label.Label) → influxdb_client.domain.label.Label
```

Create the new instance of the label as a copy existing label.

Parameters

- **cloned_name** – new label name
- **label** – existing label

Returns clonned Label

```
create_label(name: str, org_id: str, properties: Dict[str, str] = None) → influxdb_client.domain.label.Label
Create a new label.
```

Parameters

- **name** – label name
- **org_id** – organization id
- **properties** – optional label properties

Returns created label

```
delete_label(label: Union[str, influxdb_client.domain.label.Label])
Delete the label.
```

Parameters **label** – label id or Label

```
find_label_by_id(label_id: str)
Retrieve the label by id.
```

Parameters **label_id** –**Returns** Label

```
find_label_by_org(org_id) → List[influxdb_client.domain.label.Label]
Get the list of all labels for given organization.
```

Parameters **org_id** – organization id**Returns** list of labels

```
find_labels() → List[influxdb_client.domain.label.Label]
Get all available labels.
```

Returns labels

```
update_label(label: influxdb_client.domain.label.Label)
Update an existing label name and properties.
```

Parameters **label** – label**Returns** the updated label

2.6 OrganizationsApi

```
class influxdb_client.OrganizationsApi(influxdb_client)
Implementation for '/api/v2/orgs' endpoint.
```

Initialize defaults.

```
create_organization(name: str = None, organization: influxdb_client.domain.organization.Organization = None) → influxdb_client.domain.organization.Organization
Create an organization.
```

```
delete_organization(org_id: str)
Delete an organization.
```

```
find_organization(org_id)
Retrieve an organization.
```

find_organizations()

List all organizations.

me()

Return the current authenticated user.

```
class influxdb_client.domain.Organization(links=None, id=None, name=None, de-  
scription=None, created_at=None, up-  
dated_at=None, status='active')
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Organization - a model defined in OpenAPI.

created_at

Get the created_at of this Organization.

Returns The created_at of this Organization.

Return type datetime

description

Get the description of this Organization.

Returns The description of this Organization.

Return type str

id

Get the id of this Organization.

Returns The id of this Organization.

Return type str

links

Get the links of this Organization.

Returns The links of this Organization.

Return type OrganizationLinks

name

Get the name of this Organization.

Returns The name of this Organization.

Return type str

status

Get the status of this Organization.

If inactive the organization is inactive.

Returns The status of this Organization.

Return type str

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

updated_at

Get the updated_at of this Organization.

Returns The updated_at of this Organization.

Return type datetime

2.7 UsersApi

class influxdb_client.UsersApi (influxdb_client)

Implementation for '/api/v2/users' endpoint.

Initialize defaults.

create_user (name: str) → influxdb_client.domain.user.User

Create a user.

me () → influxdb_client.domain.user.User

Return the current authenticated user.

class influxdb_client.domain.User (id=None, oauth_id=None, name=None, status='active',

links=None)

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

User - a model defined in OpenAPI.

id

Get the id of this User.

Returns The id of this User.

Return type str

links

Get the links of this User.

Returns The links of this User.

Return type UserLinks

name

Get the name of this User.

Returns The name of this User.

Return type str

oauth_id

Get the oauth_id of this User.

Returns The oauth_id of this User.

Return type str

status

Get the status of this User.

If inactive the user is inactive.

Returns The status of this User.

Return type str**to_dict()**

Return the model properties as a dict.

to_str()

Return the string representation of the model.

2.8 TasksApi

class influxdb_client.TasksApi (influxdb_client)

Implementation for '/api/v2/tasks' endpoint.

Initialize defaults.

add_label (label_id: str, task_id: str) → influxdb_client.domain.label_response.LabelResponse

Add a label to a task.

add_member (member_id, task_id)

Add a member to a task.

add_owner (owner_id, task_id)

Add an owner to a task.

cancel_run (task_id: str, run_id: str)

Cancel a currently running run.

Parameters

- **task_id** –

- **run_id** –

clone_task (task: influxdb_client.domain.task.Task) → influxdb_client.domain.task.Task

Clone a task.

create_task (task: influxdb_client.domain.task.Task = None, task_create_request: influxdb_client.domain.task_create_request.TaskCreateRequest = None) → influxdb_client.domain.task.Task

Create a new task.

create_task_cron (name: str, flux: str, cron: str, org_id: str) → influxdb_client.domain.task.Task

Create a new task with cron repetition schedule.

create_task_every (name, flux, every, organization) → influxdb_client.domain.task.Task

Create a new task with every repetition schedule.

delete_label (label_id: str, task_id: str)

Delete a label from a task.

delete_member (member_id, task_id)

Remove a member from a task.

delete_owner (owner_id, task_id)

Remove an owner from a task.

delete_task (task_id: str)

Delete a task.

find_task_by_id (task_id) → influxdb_client.domain.task.Task

Retrieve a task.

find_tasks (**kwargs)

List all tasks.

Parameters

- **name** (*str*) – only returns tasks with the specified name
- **after** (*str*) – returns tasks after specified ID
- **user** (*str*) – filter tasks to a specific user ID
- **org** (*str*) – filter tasks to a specific organization name
- **org_id** (*str*) – filter tasks to a specific organization ID
- **limit** (*int*) – the number of tasks to return

Returns Tasks**find_tasks_by_user** (*task_user_id*)

List all tasks by user.

get_labels (*task_id*)

List all labels for a task.

get_logs (*task_id: str*) → List[influxdb_client.domain.log_event.LogEvent]

Retrieve all logs for a task.

Parameters **task_id** – task id**get_members** (*task_id: str*)

List all task members.

get_owners (*task_id*)

List all owners of a task.

get_run (*task_id: str, run_id: str*) → influxdb_client.domain.run.Run

Get run record for specific task and run id.

Parameters

- **task_id** – task id
- **run_id** – run id

Returns Run for specified task and run id**get_run_logs** (*task_id: str, run_id: str*) → List[influxdb_client.domain.log_event.LogEvent]

Retrieve all logs for a run.

get_runs (*task_id, **kwargs*) → List[influxdb_client.domain.run.Run]

Retrieve list of run records for a task.

Parameters

- **task_id** – task id
- **after** (*str*) – returns runs after specified ID
- **limit** (*int*) – the number of runs to return
- **after_time** (*datetime*) – filter runs to those scheduled after this time, RFC3339
- **before_time** (*datetime*) – filter runs to those scheduled before this time, RFC3339

retry_run (*task_id: str, run_id: str*)

Retry a task run.

Parameters

- **task_id** – task id
- **run_id** – run id

run_manually (task_id: str, scheduled_for: <module 'datetime' from '/home/docs/.pyenv/versions/3.6.12/lib/python3.6/datetime.py'> = None)

Manually start a run of the task now overriding the current schedule.

Parameters

- **task_id** –
- **scheduled_for** – planned execution

update_task (task: influxdb_client.domain.task.Task) → influxdb_client.domain.task.Task

Update a task.

update_task_request (task_id, task_update_request: influxdb_client.domain.task_update_request.TaskUpdateRequest) → influxdb_client.domain.task.Task

Update a task.

```
class influxdb_client.domain.Task(id=None, type=None, org_id=None, org=None,
                                    name=None, description=None, status=None, la-
                                    bels=None, authorization_id=None, flux=None,
                                    every=None, cron=None, offset=None, lat-
                                    est_completed=None, last_run_status=None,
                                    last_run_error=None, created_at=None, up-
                                    dated_at=None, links=None)
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Task - a model defined in OpenAPI.

authorization_id

Get the authorization_id of this Task.

The ID of the authorization used when this task communicates with the query engine.

Returns The authorization_id of this Task.

Return type str

created_at

Get the created_at of this Task.

Returns The created_at of this Task.

Return type datetime

cron

Get the cron of this Task.

A task repetition schedule in the form ‘* * * * *’; parsed from Flux.

Returns The cron of this Task.

Return type str

description

Get the description of this Task.

An optional description of the task.

Returns The description of this Task.

Return type str

every

Get the every of this Task.

A simple task repetition schedule; parsed from Flux.

Returns The every of this Task.

Return type str

flux

Get the flux of this Task.

The Flux script to run for this task.

Returns The flux of this Task.

Return type str

id

Get the id of this Task.

Returns The id of this Task.

Return type str

labels

Get the labels of this Task.

Returns The labels of this Task.

Return type list[Label]

last_run_error

Get the last_run_error of this Task.

Returns The last_run_error of this Task.

Return type str

last_run_status

Get the last_run_status of this Task.

Returns The last_run_status of this Task.

Return type str

latest_completed

Get the latest_completed of this Task.

Timestamp of latest scheduled, completed run, RFC3339.

Returns The latest_completed of this Task.

Return type datetime

links

Get the links of this Task.

Returns The links of this Task.

Return type TaskLinks

name
Get the name of this Task.
The name of the task.

Returns The name of this Task.

Return type str

offset
Get the offset of this Task.
Duration to delay after the schedule, before executing the task; parsed from flux, if set to zero it will remove this option and use 0 as the default.

Returns The offset of this Task.

Return type str

org
Get the org of this Task.
The name of the organization that owns this Task.

Returns The org of this Task.

Return type str

org_id
Get the org_id of this Task.
The ID of the organization that owns this Task.

Returns The org_id of this Task.

Return type str

status
Get the status of this Task.

Returns The status of this Task.

Return type TaskStatusType

to_dict()
Return the model properties as a dict.

to_str()
Return the string representation of the model.

type
Get the type of this Task.
The type of task, this can be used for filtering tasks on list actions.

Returns The type of this Task.

Return type str

updated_at
Get the updated_at of this Task.

Returns The updated_at of this Task.

Return type datetime

2.9 DeleteApi

```
class influxdb_client.DeleteApi (influxdb_client)
    Implementation for '/api/v2/delete' endpoint.

    Initialize defaults.

    delete (start: <module 'datetime' from '/home/docs/pyenv/versions/3.6.12/lib/python3.6/datetime.py'>,
              stop: object, predicate: object, bucket: str, org: str) → None
        Delete Time series data from InfluxDB.
```

Parameters

- **start** – start time
- **stop** – stop time
- **predicate** – predicate
- **bucket** – bucket id or name from which data will be deleted
- **org** – organization id or name

Returns

```
class influxdb_client.domain.DeletePredicateRequest (start=None, stop=None, predicate=None)
```

NOTE: This class is auto generated by OpenAPI Generator.

Ref: <https://openapi-generator.tech>

Do not edit the class manually.

DeletePredicateRequest - a model defined in OpenAPI.

predicate

Get the predicate of this DeletePredicateRequest.

InfluxQL-like delete statement

Returns The predicate of this DeletePredicateRequest.

Return type str

start

Get the start of this DeletePredicateRequest.

RFC3339Nano

Returns The start of this DeletePredicateRequest.

Return type datetime

stop

Get the stop of this DeletePredicateRequest.

RFC3339Nano

Returns The stop of this DeletePredicateRequest.

Return type datetime

to_dict()

Return the model properties as a dict.

to_str()

Return the string representation of the model.

InfluxDB 2.0 python client library.

Note: Use this client library with InfluxDB 2.x and InfluxDB 1.8+. For connecting to InfluxDB 1.7 or earlier instances, use the [influxdb-python client library](#).

CHAPTER 3

InfluxDB 2.0 client features

- **Querying data**
 - using the Flux language
 - into csv, raw data, `flux_table` structure, Pandas DataFrame
 - *How to queries*
- **Writing data using**
 - Line Protocol
 - Data Point
 - RxPY Observable
 - Pandas DataFrame
 - *How to writes*
- **InfluxDB 2.0 API client for management**
 - the client is generated from the `swagger` by using the `openapi-generator`
 - organizations & users management
 - buckets management
 - tasks management
 - authorizations
 - health check
 - ...
- ‘**InfluxDB 1.8 API compatibility**’
- **Examples**
 - ‘**Connect to InfluxDB Cloud**’
 - ‘**How to efficiently import large dataset**’

- ‘[Efficiency write data from IOT sensor](#)‘_
- ‘[How to use Jupyter + Pandas + InfluxDB 2](#)‘_
- Advanced Usage
 - ‘[Gzip support](#)‘_
 - ‘[Delete data](#)‘_

CHAPTER 4

Installation

InfluxDB python library uses RxPY - The Reactive Extensions for Python (RxPY).

Python 3.6 or later is required.

Note: It is recommended to use ciso8601 with client for parsing dates. ciso8601 is much faster than built-in Python datetime. Since it's written as a C module the best way is build it from sources:

Windows:

You have to install Visual C++ Build Tools 2015 to build ciso8601 by pip.

conda:

Install from sources: conda install -c conda-forge/label/cf202003 ciso8601.

4.1 pip install

The python package is hosted on PyPI, you can install latest version directly:

```
pip install influxdb-client[ciso]
```

Then import the package:

```
import influxdb_client
```

4.2 Setuptools

Install via Setuptools.

```
python setup.py install --user
```

(or sudo python setup.py install to install the package for all users)

CHAPTER 5

Getting Started

Please follow the [Installation](#) and then run the following:

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:8086", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, record=p)

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print (row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1
```


CHAPTER 6

Client configuration

6.1 Via File

A client can be configured via `*.ini` file in segment `influx2`.

The following options are supported:

- `url` - the url to connect to InfluxDB
- `org` - default destination organization for writes and queries
- `token` - the token to use for the authorization
- `timeout` - socket timeout in ms (default value is 10000)
- `verify_ssl` - set this to false to skip verifying SSL certificate when calling API from https server
- `ssl_ca_cert` - set this to customize the certificate file to verify the peer
- `connection_pool_maxsize` - set the number of connections to save that can be reused by urllib3

```
self.client = InfluxDBClient.from_config_file("config.ini")
```

6.2 Via Environment Properties

A client can be configured via environment properties.

Supported properties are:

- `INFLUXDB_V2_URL` - the url to connect to InfluxDB
- `INFLUXDB_V2_ORG` - default destination organization for writes and queries
- `INFLUXDB_V2_TOKEN` - the token to use for the authorization
- `INFLUXDB_V2_TIMEOUT` - socket timeout in ms (default value is 10000)

- `INFLUXDB_V2_VERIFY_SSL` - set this to false to skip verifying SSL certificate when calling API from https server
- `INFLUXDB_V2_SSL_CA_CERT` - set this to customize the certificate file to verify the peer
- `INFLUXDB_V2_CONNECTION_POOL_MAXSIZE` - set this to customize the certificate file to verify the peer

```
self.client = InfluxDBClient.from_env_properties()
```

CHAPTER 7

Indices and tables

- genindex
- modindex
- search

Index

A

add_label () (*influxdb_client.TasksApi method*), 26
add_member () (*influxdb_client.TasksApi method*), 26
add_owner () (*influxdb_client.TasksApi method*), 26
authorization_id (*influxdb_client.domain.Task attribute*), 28
authorizations_api () (*influxdb_client.InfluxDBClient method*), 16

B

Bucket (*class in influxdb_client.domain*), 21
buckets_api () (*influxdb_client.InfluxDBClient method*), 16
BucketsApi (*class in influxdb_client*), 20

C

cancel_run () (*influxdb_client.TasksApi method*), 26
clone_label () (*influxdb_client.LabelsApi method*), 22
clone_task () (*influxdb_client.TasksApi method*), 26
close () (*influxdb_client.InfluxDBClient method*), 16
close () (*influxdb_client.WriteApi method*), 20
create_bucket () (*influxdb_client.BucketsApi method*), 20
create_label () (*influxdb_client.LabelsApi method*), 22
create_organization () (*influxdb_client.OrganizationsApi method*), 23
create_task () (*influxdb_client.TasksApi method*), 26
create_task_cron () (*influxdb_client.TasksApi method*), 26
create_task_every () (*influxdb_client.TasksApi method*), 26
create_user () (*influxdb_client.UsersApi method*), 25
created_at (*influxdb_client.domain.Bucket attribute*), 21

created_at (*influxdb_client.domain.Organization attribute*), 24
created_at (*influxdb_client.domain.Task attribute*), 28
cron (*influxdb_client.domain.Task attribute*), 28

D

delete () (*influxdb_client.DeleteApi method*), 31
delete_api () (*influxdb_client.InfluxDBClient method*), 16
delete_bucket () (*influxdb_client.BucketsApi method*), 20
delete_label () (*influxdb_client.LabelsApi method*), 23
delete_label () (*influxdb_client.TasksApi method*), 26
delete_member () (*influxdb_client.TasksApi method*), 26
delete_organization () (*influxdb_client.OrganizationsApi method*), 23
delete_owner () (*influxdb_client.TasksApi method*), 26
delete_task () (*influxdb_client.TasksApi method*), 26
DeleteApi (*class in influxdb_client*), 31
DeletePredicateRequest (*class in influxdb_client.domain*), 31
description (*influxdb_client.domain.Bucket attribute*), 21
description (*influxdb_client.domain.Organization attribute*), 24
description (*influxdb_client.domain.Task attribute*), 28

E

every (*influxdb_client.domain.Task attribute*), 29

F

find_bucket_by_id () (*influxdb_client.BucketsApi*

method), 21
find_bucket_by_name() (influxdb_client.BucketsApi method), 21
find_buckets() (influxdb_client.BucketsApi method), 21
find_label_by_id() (influxdb_client.LabelsApi method), 23
find_label_by_org() (influxdb_client.LabelsApi method), 23
find_labels() (influxdb_client.LabelsApi method), 23
find_organization() (influxdb_client.OrganizationsApi method), 23
find_organizations() (influxdb_client.OrganizationsApi method), 23
find_task_by_id() (influxdb_client.TasksApi method), 26
find_tasks() (influxdb_client.TasksApi method), 26
find_tasks_by_user() (influxdb_client.TasksApi method), 27
flush() (influxdb_client.WriteApi method), 20
flux (influxdb_client.domain.Task attribute), 29
from_config_file() (influxdb_client.InfluxDBClient class method), 16
from_env_properties() (influxdb_client.InfluxDBClient class method), 17

G
get_labels() (influxdb_client.TasksApi method), 27
get_logs() (influxdb_client.TasksApi method), 27
get_members() (influxdb_client.TasksApi method), 27
get_owners() (influxdb_client.TasksApi method), 27
get_run() (influxdb_client.TasksApi method), 27
get_run_logs() (influxdb_client.TasksApi method), 27
get_runs() (influxdb_client.TasksApi method), 27

H
health() (influxdb_client.InfluxDBClient method), 17

I
id (influxdb_client.domain.Bucket attribute), 21
id (influxdb_client.domain.Organization attribute), 24
id (influxdb_client.domain.Task attribute), 29
id (influxdb_client.domain.User attribute), 25
InfluxDBClient (class in influxdb_client), 15

L
labels (influxdb_client.domain.Bucket attribute), 21
labels (influxdb_client.domain.Task attribute), 29
labels_api() (influxdb_client.InfluxDBClient method), 17
LabelsApi (class in influxdb_client), 22
last_run_error (influxdb_client.domain.Task attribute), 29
last_run_status (influxdb_client.domain.Task attribute), 29
latest_completed (influxdb_client.domain.Task attribute), 29
links (influxdb_client.domain.Bucket attribute), 21
links (influxdb_client.domain.Organization attribute), 24
links (influxdb_client.domain.Task attribute), 29
links (influxdb_client.domain.User attribute), 25

M
me () (influxdb_client.OrganizationsApi method), 24
me () (influxdb_client.UsersApi method), 25

N
name (influxdb_client.domain.Bucket attribute), 21
name (influxdb_client.domain.Organization attribute), 24
name (influxdb_client.domain.Task attribute), 29
name (influxdb_client.domain.User attribute), 25

O
oauth_id (influxdb_client.domain.User attribute), 25
offset (influxdb_client.domain.Task attribute), 30
org (influxdb_client.domain.Task attribute), 30
org_id (influxdb_client.domain.Bucket attribute), 22
org_id (influxdb_client.domain.Task attribute), 30
Organization (class in influxdb_client.domain), 24
organizations_api() (influxdb_client.InfluxDBClient method), 17
OrganizationsApi (class in influxdb_client), 23

P
predicate (influxdb_client.domain.DeletePredicateRequest attribute), 31

Q
query() (influxdb_client.QueryApi method), 18
query_api() (influxdb_client.InfluxDBClient method), 17
query_csv() (influxdb_client.QueryApi method), 18
query_data_frame() (influxdb_client.QueryApi method), 19
query_data_frame_stream() (influxdb_client.QueryApi method), 19
query_raw() (influxdb_client.QueryApi method), 19
query_stream() (influxdb_client.QueryApi method), 19

QueryApi (*class in influxdb_client*), 18

R

ready () (*influxdb_client.InfluxDBClient method*), 18
 retention_rules (*influxdb_client.domain.Bucket attribute*), 22
 retry_run () (*influxdb_client.TasksApi method*), 27
 rp (*influxdb_client.domain.Bucket attribute*), 22
 run_manually () (*influxdb_client.TasksApi method*), 28

S

start (*influxdb_client.domain.DeletePredicateRequest attribute*), 31
 status (*influxdb_client.domain.Organization attribute*), 24
 status (*influxdb_client.domain.Task attribute*), 30
 status (*influxdb_client.domain.User attribute*), 25
 stop (*influxdb_client.domain.DeletePredicateRequest attribute*), 31

T

Task (*class in influxdb_client.domain*), 28
 tasks_api () (*influxdb_client.InfluxDBClient method*), 18
 TasksApi (*class in influxdb_client*), 26
 to_dict () (*influxdb_client.domain.Bucket method*), 22
 to_dict () (*influxdb_client.domain.DeletePredicateRequest method*), 31
 to_dict () (*influxdb_client.domain.Organization method*), 24
 to_dict () (*influxdb_client.domain.Task method*), 30
 to_dict () (*influxdb_client.domain.User method*), 26
 to_str () (*influxdb_client.domain.Bucket method*), 22
 to_str () (*influxdb_client.domain.DeletePredicateRequest method*), 31
 to_str () (*influxdb_client.domain.Organization method*), 24
 to_str () (*influxdb_client.domain.Task method*), 30
 to_str () (*influxdb_client.domain.User method*), 26
 type (*influxdb_client.domain.Bucket attribute*), 22
 type (*influxdb_client.domain.Task attribute*), 30

U

update_label () (*influxdb_client.LabelsApi method*), 23
 update_task () (*influxdb_client.TasksApi method*), 28
 update_task_request () (*influxdb_client.TasksApi method*), 28
 updated_at (*influxdb_client.domain.Bucket attribute*), 22

updated_at (*influxdb_client.domain.Organization attribute*), 24

updated_at (*influxdb_client.domain.Task attribute*), 30

User (*class in influxdb_client.domain*), 25

users_api () (*influxdb_client.InfluxDBClient method*), 18

UsersApi (*class in influxdb_client*), 25

W

write () (*influxdb_client.WriteApi method*), 20
 write_api () (*influxdb_client.InfluxDBClient method*), 18

WriteApi (*class in influxdb_client*), 19